

ZC-015 Bulk

Description

D-5015 NS is a light lubricant that forms a soft, ultra thin protective film to prevent corrosion and disperse water. It is for short-term use on critical metal surfaces in avionics, electrical and electronic components. D-5015 NS is safe for use on most paints, plastics and insulation.

Application

D-5015NS displaces water from electrical and electronic components and provides a thin protective barrier coating that helps prevent corrosion and fungus growth. Excellent for “overnight” tooling protection on highly critical surfaces.

Physical Properties

Flash Point: None
Boiling Range: -22 to 375 °F
Vapor Density: Heavier than air
Specific Gravity (H₂O=1): 0.9
Evaporation Rate: Faster than ether
Material V.O.C.: 514g/l

MilSpec

MIL-C-81309 Ty III CL-1&2,
NSN: 8030-00-546-8637

Other

Sikorsky SS 8536 Ty I

Features

Safe on most paints, plastics or insulation.
Light, soft film provides lubrication for moving parts.
Ideal for in field service use.
Excellent for electrical and electronic components.

Specifications

QPL MIL-C-81309E
Type III Class 2 (aerosol)
Type III Class 1 (bulk)
SIKORSKY SS8536
NSN 8030-00-546-8637

Packaging

Aerosol, quarts, gallons, 5 gallons, drums.
Special packaging upon request

Commercial Specifications