

D-5440NS*Product description:***FLUOROCARBON DRY LUBRICANT
ZERO OZONE DEPLETING****FEATURES:**

- ▶ A fluorocarbon telomer that is chemically similar to the PTFE-fluorocarbon resin

AVAILABLE PACK SIZES:

- ▶ Aerosol-002060]
- ▶ Quarts-009660]
- ▶ Gallons (Case of 4)-007070]
- ▶ 5 Gallon Pail-007071]
- ▶ 55 Gallon Drum-007072]
- ▶ Special Packaging Upon Request]

KEY BENEFITS:

- ▶ Does not run or stain
- ▶ Excellent dry film lubricant for wood, plastic, rubber, paper, and metal
- ▶ Non-conductive and chemically inert in use
- ▶ Prevents corrosion on metal substrates and provides a lubricating surface for them
- ▶ Excellent anti-stick properties

Rev: 20065B
08-16-2021

D-5440NS*Product description:***FLUOROCARBON DRY LUBRICANT
ZERO OZONE DEPLETING****KEY BENEFITS:**

- ▶ Withstands temperatures that range from cryogenic to 240°F (116°C)
- ▶ Finds many uses throughout the aircraft
- ▶ Effective release agent for epoxies, polyurethanes, etc
- ▶ Provides substrate with highest adhesion possible while providing lubricating properties or a good release

SPECS:

- DMS 1762, Type 7E
- DPM 3494 - Release Agent
- UAL LUB 4500-1750
- SCE 898-13117
- NSN: 9150-01-545-0801 (Aerosol)
- T.O. 1C-130H-2-12JG-20-1
- T.O. 1C-130J-2-12JG-20-1

APPLICATIONS:

- ✓ **D-5440NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated
- ✓ Used as a dry film lubricant or mold release where it is applied to a cold or warm surface (less than 240°F)
- ✓ Currently being used on slat tracks to prevent corrosion and provide lubrication without the buildup of debris that is typically found if greases and oils are used
- ✓ The aerosol form of the **D-5440NS** Fluorocarbon is designed primarily to be used as a dry film lubricant or mold release where it is applied to a cold or warm surface (less than 240°F).
- ✓ Bulk application available as **ZC-440**



For more information contact us :
zipchem@addevmaterials.com



Part of

**ADDEV MATERIALS**