

ZC-440**Product description:****FLUOROCARBON DRY LUBRICANT****FEATURES:**

- ▶ A fluorocarbon telomer that is chemically similar to the PTFE-fluorocarbon resin

KEY BENEFITS:

- ▶ Aerosol-002060]
- ▶ Quarts-009660]
- ▶ Gallons-007070]
- ▶ 5 Gallon Pail-007071]
- ▶ 55 Gallon Drum-007072]
- ▶ Special Packaging Upon Request]

KEY BENEFITS:

- ▶ Does not run or stain
- ▶ Excellent dry film lubricant for wood, plastic, rubber, paper, and metal
- ▶ Prevents corrosion on metal substrates and provides a lubricating surface for them
- ▶ Excellent anti-stick properties
- ▶ Non-flammable
- ▶ Non-conductive and chemically inert in use
- ▶ Withstands temperatures up to 500°F (260°C) continuously

Rev: 29128C
08-16-2021

The logo for Aero-Lube, featuring the brand name in a bold, sans-serif font with a trademark symbol. The background of the entire page is a photograph of an aircraft engine in a hangar.

LUBRICANTS & LUBRICATING COMPOUNDS

ZC-440



Product description:

FLUOROCARBON DRY LUBRICANT

KEY BENEFITS:

- ▶ Finds many uses throughout the aircraft
- ▶ Withstands cryogenic temperatures
- ▶ Provides substrate with highest adhesion possible while providing lubricating properties or a good release

APPLICATIONS:

- ✓ Aerosol application available as **D-5440NS**
- ✓ Used as a dry film lubricant or mold release where it is applied to a cold or warm surface (less than 240°F)
- ✓ Applied on slat tracks to prevent corrosion and provide lubrication without the buildup of debris that is typically found if greases and oils are used
- ✓ Agitate constantly if using this material in bulk form

 For more information contact us :
zipchem@addevmaterials.com

