

Cor-Ban®

CORROSION INHIBITING COMPOUNDS

COR-BAN® 35



Product description: CORROSION INHIBITING COMPOUND

FEATURES:

- ▶ A long lasting, high solids, low volatile, high penetration, and water displacing corrosion inhibiting compound
- ▶ Non-tacky with a light, transparent, reddish-pink tint



KEY BENEFITS:

- ▶ Non-cracking and flaking to -40°F (-40°C)
- ▶ Low VOC
- ▶ Detectable and non-sagging thixotropic film
- ▶ Fast drying
- ▶ Solvent removable
- ▶ Water displacing
- ▶ High penetration
- ▶ Very low dry film weight (< 1 mil required to surpass specification)
- ▶ > 2000 hours salt spray
- ▶ High Solids: >51%

SPECS:

- AIMS 09-08-002 Type II Gr 2 (Meets requirements)
- AIMS 09-08-003 (On Airbus CML)
- ATR 42/ATR 72 SRM

Rev: 20066E
09-15-2021

 For more information contact us :
zipchem@addevmaterials.com



COR-BAN® 35



Product description: CORROSION INHIBITING COMPOUND

SPECS:

- BAE: AVP 2-022
- BMS 3-23F Type II (Meets requirements)
- BMS 3-29 (Meets requirements)
- BMS 3-35B (On Boeing QPL)
- Boeing DMS 2150
- Bombardier BAMS 565-006 Type I & Type II
- Cessna CSNP038 Type IVA / Class 2
- Dassault DGQT 1.7.0.0103
- de Havilland DHMS C 4.12
- Embraer 51-61-00 Type I & Type II
- FedEx A30-51-001
- Gulfstream GAC115AD (Meets requirements)
- MEP 10-063
- Mil-DTL-85054D (QPL)
- NSN: 6850-01-492-2932, 8030-01-531-7358 (Aerosols) (Meets Requirements)
- NSN: 8030-01-615-4740 (Gallons) (Meets Requirements)
- NSN: 8030-01-659-2958 (1 Gallon) (Meets Requirements)
- NSN: 8030-01-531-7360 (5 Gallons) (Meets Requirements)
- NSN: 8030-01-615-4733 (8oz Brush In Cap) (Meets Requirements)
- NSN: 8030-01-615-4737 (Quart) (Meets Requirements)
- SIKORSKY SS 8536 Type II
- Sukhoi RRJ0000-RE-811-2559
- Viking VMS C4.12

APPLICATIONS:

- ✓ Apply by using conventional airless or air-operated spray equipment or by using aerosol
- ✓ Apply at 1 - 1½ mils (25-38 microns) wet thickness
- ✓ The **Cor-Ban® 35** aerosol can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated
- ✓ Use on high profile aircraft substrates; upper edge floor beams, wheel wells, pressure deck, and center wing sections
- ✓ All properties represented were achieved with a dry film thickness of 0.5-0.75 mils (12-19 microns)

COR-BAN® 35



Product description:
**CORROSION INHIBITING
COMPOUND**

APPLICATIONS:

- ✓ One aerosol can covers approximately 95 ft² (8.8 m²)
- ✓ 1 gallon of bulk material can covers approximately 1600 ft² (39.3 m² per liter)
- ✓ Cured Cor-Ban® 35 can be removed with Sur-Prep® 3167, Sur-Prep® 3160, or Zip-Strip™ 125M

PHYSICAL PROPERTIES:

- ▶ **Flash Point:** 115°F (46°)
- ▶ **Specific Gravity:** 0.90
- ▶ **Water Displacement:** 0% Rust
- ▶ **Non-Volatiles:** 51% min.
- ▶ **Material VOC:** 395 g/L
- ▶ **Drying Time:** <1 hour
- ▶ **Color:** Transparent reddish-pink
- ▶ **Exfoliation:** Pass
- ▶ **Solvent Type:** Aliphatic
- ▶ **Low Temp Flaking:** Pass
- ▶ **Penetration:** BMS 3-23G pass
- ▶ **Compatibility Cd, Mg, Al:** Pass
- ▶ **Operating Temperature:** -65°F (-54°C) to 350°F (177°C)



Cor-Ban®

CORROSION INHIBITING COMPOUNDS

COR-BAN® 35



Product description:
**CORROSION INHIBITING
COMPOUND**

AVAILABLE PACK SIZES:

- ▶ Aerosol-004675]
- ▶ 8 oz Brush In Cap-010884]
- ▶ Quarts-009408]
- ▶ Gallons-009409]
- ▶ 5 Gallon Pail-002104]
- ▶ 55 Gallon Drum-002105]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEVMATERIALS