

ZC-029



Product description:
**CORROSION INHIBITING
COMPOUND**

FEATURES:

- ▶ A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- ▶ Non-tacky with a light amber tint

KEY BENEFITS:

- ▶ > 1500 hours salt spray on aluminum (Al)
- ▶ Fast drying and non-tacky
- ▶ Non-cracking and flaking up to -40°F
- ▶ Has a detectable film
- ▶ Solvent removable
- ▶ Very low dry weight film
- ▶ High Solids > 51%

SPECS:

- BMS 3-29
- DMS 2150 Type 1 & Type 2

- NSN: 8030-01-501-6622
- NSN: 6850-01-355-3387



Rev: 29087F
09-28-2021

ZC-029



Product description:
**CORROSION INHIBITING
COMPOUND**

APPLICATIONS:

- ✓ Apply via airless or air-operated spray equipment
 - ✓ Apply at 2-3 mils of wet thickness
 - ✓ Aerosol application available as **D-5029NS**
 - ✓ Use on high profile aircraft substrates
-

PHYSICAL PROPERTIES:

- ▶ **Color:** Transparent Amber
- ▶ **Drying Time:** <12 hours
- ▶ **Flash Point:** 122°F
- ▶ **Non-Volatiles:** 51% min.
- ▶ **Specific Gravity:** 0.89
- ▶ **Viscosity:** 140 cps.
- ▶ **Water Displacement:** 0% Rust



Cor-Ban®

CORROSION INHIBITING COMPOUNDS

ZC-029



Product description:
**CORROSION INHIBITING
COMPOUND**

AVAILABLE PACK SIZES:

- ▶ Aerosol-002050]
- ▶ Gallons-009422]
- ▶ 5 Gallon Pail-002109]
- ▶ 55 Gallon Drum-002110]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEVMATERIALS