

D-5029NS



Product description:
**CORROSION INHIBITING
COMPOUND BMS 3-29**

FEATURES:

- ▶ A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- ▶ Non-tacky with a light, amber tint

KEY BENEFITS:

- ▶ Fast drying and non-tacky
- ▶ Non-cracking and flaking up to -40°F
- ▶ Contains a detectable film
- ▶ Solvent removable
- ▶ > 1500 hours of salt spray
- ▶ High Solids > 51%

SPECS:

- BMS 3-29 (Meets or Exceeds)
- DMS 2150 Type 1 & Type 2 (Meets or Exceeds)
- NSN: 8030-01-501-6622 (Meets or Exceeds)
- NSN: 6850-01-355-3387 (Meets or Exceeds)



Rev: 29089B
10-11-2021

D-5029NS



Product description:
**CORROSION INHIBITING
COMPOUND BMS 3-29**

APPLICATIONS:

- ✓ Use **D-5029NS** on high profile aircraft substrates
- ✓ Easily apply corrosion inhibiting compound via aerosol
- ✓ **D-5029NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated.
- ✓ Apply at 2-3 mils of wet thickness
- ✓ One aerosol can coats approximately 50 ft²
- ✓ Bulk application available as **ZC-029**

PHYSICAL PROPERTIES:

- ▶ **Color:** Transparent Amber
- ▶ **Drying Time:** <12 hours
- ▶ **Flash Point:** 122°F
- ▶ **Non-Volatiles:** 51% min.
- ▶ **Specific Gravity:** 0.89
- ▶ **Viscosity:** 140 cps.
- ▶ **Water Displacement:** 0% Rust



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEVMATERIALS



Cor-Ban®

CORROSION INHIBITING COMPOUNDS

D-5029NS



Product description:
**CORROSION INHIBITING
COMPOUND BMS 3-29**

AVAILABLE PACK SIZES:

- ▶ Aerosol-002050]
- ▶ Gallons-009422]
- ▶ 5 Gallon Pail-002109]
- ▶ 55 Gallon Drum-002110]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV MATERIALS