

D-5261NS



Product description:

CLEANER LUBRICANT PENETRANT

FEATURES:

- ▶ A special formulation of oil formulation that conforms to Mil-PRF-7870D.

KEY BENEFITS:

- ▶ Provides superior resistance to oxidation
 - ▶ Ensures that parts, especially metals, do not rust
 - ▶ Limits galvanic corrosion from occurring, especially on dissimilar metal assemblies
 - ▶ **D-5261NS** can be used over temperatures from -65°F to 250°F
 - ▶ Prevents corrosion on metals
- ▶ A very effective cleaner and penetrating lubricant
 - ▶ Penetrates tight parts (ie: heart strands of cables) and deposits a rust preventive lubricating film



SPECS:

- MIL-PRF-7870D (Oil used in **D-5261NS**)

APPLICATIONS:

- ✓ **D-5261NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated.

Rev: 29110D
10-07-2021

D-5261NS*Product description:***CLEANER LUBRICANT PENETRANT****APPLICATIONS:**

- ✓ Use on aircraft flight controls, engine and landing gear cables, pulleys, pressure seals, cargo hoist cables, cargo restraining system components, door interlock actuating mechanisms, slide mechanisms, hinges, and static joints
- ✓ Available in bulk as **ZC-5261**

PHYSICAL PROPERTIES:

- ▶ **Evaporation Rate:** Faster than ether
- ▶ **Flash Point of Oil:** 300°F
- ▶ **Specific Gravity (H₂O=1):** 0.88
- ▶ **Temperature Range:** -65°F to 250°F
- ▶ **Vapor Density:** Heavier than air
- ▶ **Viscosity @ 100°F:** Min. 10 cst.

AVAILABLE PACK SIZES:

- ▶ Aerosol-002056]
- ▶ Gallons-009425]
- ▶ 5 Gallon Pail-002138]
- ▶ Special Packaging Upon Request]