

D-5440NS



Product description:

FLUOROCARBON DRY LUBRICANT ZERO OZONE DEPLETING

FEATURES:

- ▶ A fluorocarbon telomer that is chemically similar to the PTFE-fluorocarbon resin

KEY BENEFITS:

- ▶ Does not run or stain
- ▶ Excellent dry film lubricant for wood, plastic, rubber, paper, and metal
- ▶ Non-conductive and chemically inert
- ▶ Prevents corrosion on metal substrates and provides a lubricating surface for them
- ▶ Excellent anti-stick properties
- ▶ Withstands temperatures that range from cryogenic to 240°F (116°C)
- ▶ Low coefficient of friction
- ▶ Finds many uses throughout the aircraft
- ▶ Effective release agent for epoxies, polyurethanes, etc
- ▶ Provides substrate with highest adhesion possible while providing lubricating properties or a good release



Rev: 20065C
10-07-2021

D-5440NS*Product description:***FLUOROCARBON DRY LUBRICANT
ZERO OZONE DEPLETING****SPECS:**

- DMS 1762, Type 7E (Qualified to spec and callout)
- DPM 3494 - Release Agent (Qualified to spec and callout)
- UAL LUB 4500-1750 (Qualified to spec and callout)
- SCE 898-13117 (Qualified to spec and callout)
- NSN: 9150-01-545-0801 (Aerosol) (Qualified to spec and callout)
- T.O. 1C-130H-2-12JG-20-1 (Qualified to spec and callout)
- T.O. 1C-130J-2-12JG-20-1 (Qualified to spec and callout)

APPLICATIONS:

- ✓ **D-5440NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated
- ✓ Currently being used on slat tracks to prevent corrosion and provide lubrication without the buildup of debris that is typically found if greases and oils are used
- ✓ The aerosol form of the **D-5440NS** Fluorocarbon is designed primarily to be used as a dry film lubricant or mold release where it is applied to a cold or warm surface (less than 240°F).
- ✓ Bulk application available as **ZC-440**

PHYSICAL PROPERTIES:

- ▶ **Coefficient of Friction:** 0.06 to 0.09 (Static)
- ▶ **Density:** 7.7 lbs/gal
- ▶ **Fungal Growth per Fed-STD-810 Method 508.7:** 0 (No Microbial Growth)



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV MATERIALS

The logo for Aero-Lube, featuring the brand name in a bold, sans-serif font with a trademark symbol. The background of the entire page is a photograph of an aircraft engine in a hangar.

LUBRICANTS & LUBRICATING COMPOUNDS

D-5440NS



Product description:

**FLUOROCARBON DRY LUBRICANT
ZERO OZONE DEPLETING**

PHYSICAL PROPERTIES:

- ▶ **Intermittent Temperature:** 240°F (116°C)
- ▶ **Service Temperature:** 180°F (82°C)

AVAILABLE PACK SIZES:

- ▶ Aerosol-002060]
- ▶ Quarts-009660]
- ▶ Gallons (Case of 4)-007070]
- ▶ 5 Gallon Pail-007071]
- ▶ 55 Gallon Drum-007072]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV MATERIALS