

D-5460NS



Product description:

MOLY DRI-LUBE ZERO OZONE DEPLETING

FEATURES:

- ▶ A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- ▶ Contains a dry film
- ▶ An extreme pressure lube



KEY BENEFITS:

- ▶ Excellent high temperature stability
- ▶ Good surface adhesion
- ▶ Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- ▶ Contains a fast air drying formula
- ▶ Has a clean and uncontaminated delivery system
- ▶ Formulation yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)

SPECS:

- GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC
- NSN: 9150-01-057-2576 (Aerosol)

Rev: 20067G
10-08-2021

D-5460NS*Product description:***MOLY DRI-LUBE ZERO OZONE
DEPLETING****APPLICATIONS:**

- ✓ **D-5460NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated
- ✓ Bulk application available as **ZC-460**
- ✓ Originally formulated for DC-8 flap track fairings
- ✓ **D-5460NS** is used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser pre-cooler duct seal lubrication

PHYSICAL PROPERTIES:

- ▶ **Average Particle Size:** MoS₂ 0.4 Microns
- ▶ **Boundary Lubrication:** 660°F (350°C)
- ▶ **Coefficient of Friction:** 0.23 (Static)
- ▶ **Color:** Gray
- ▶ **Fungal Growth per Fed-STD-810 Method 508.7:** 0 (No Microbial Growth)
- ▶ **Service Temperature:** 390°F (200°C)

The logo for Aero-Lube, featuring the brand name in a bold, sans-serif font with a trademark symbol. The background of the entire page is a photograph of an aircraft engine in a hangar.

LUBRICANTS & LUBRICATING COMPOUNDS

D-5460NS



Product description:

**MOLY DRI-LUBE ZERO OZONE
DEPLETING**

AVAILABLE PACK SIZES:

- ▶ Aerosol-002061]
- ▶ Gallons-002318]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV MATERIALS