

D-5480NS



Product description: **GRAPHITE DRY LUBRICANT**

FEATURES:

- ▶ A colloidal graphite dispersion in a thermoplastic resin
- ▶ The aerosol application of the **D-5480NS Graphite** produces an extremely tenacious dry film of fine particle size graphite on the surface to be lubricated
- ▶ Dries rapidly at room temperature

KEY BENEFITS:

- ▶ Does not contain grease, wax or silicone
- ▶ Forms a stable film that can withstand continuous temperatures of 400°F (204°C) to 850°F (454°C) for limited time periods
- ▶ **D-5480NS** has strong properties for plating non-conductors

SPECS:

- ASTM F945
- LUB 4500-35C

APPLICATIONS:

- ✓ Bulk application available as **ZC-480**



Rev: 29095E
10-08-2021

D-5480NS**Product description:**
GRAPHITE DRY LUBRICANT**APPLICATIONS:**

- ✓ **D-5480NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated.
- ✓ Apply on:
 - Air Conditioning and Heating Duct Controls
 - Internal Combustion Engines
 - Bearings
 - Conveyer Components
 - Dyes
 - O-Rings
 - Pistons
 - Gears
 - Hoists
 - Locks
 - Chains
 - Non-Conductor Plating
 - Flatleaf Springs
 - Gaskets
 - Plating Printing Circuits
 - Tools

PHYSICAL PROPERTIES:

- ▶ **Color:** Black
- ▶ **Density:** 7.5 lbs / gal
- ▶ **Friction Coefficient:** 0.19 (static)
- ▶ **Service Temperature:** 400°F (204°C)
- ▶ **Intermittent Temperature:** 850°F (454°C)



For more information contact us :
zipchem@addevmaterials.com



Part of

**ADEV MATERIALS**



Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

D-5480NS



Product description:

GRAPHITE DRY LUBRICANT

AVAILABLE PACK SIZES:

- ▶ Aerosol-002062]
- ▶ Gallons-100437]
- ▶ 5 Gallon Pail-100438]
- ▶ Special Packaging Upon Request]



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEVMATERIALS