

Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

ZC-460



Product description:

MOLY DRI-LUBE

FEATURES:

- ▶ A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- ▶ Contains a dry film
- ▶ An extreme pressure lube

KEY BENEFITS:

- ▶ Excellent high temperature stability
- ▶ Good surface adhesion
- ▶ Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- ▶ Contains a fast drying formula
- ▶ Yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)

SPECS:

- GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC

APPLICATIONS:

- ✓ Aerosol application available as **D-5460NS**
- ✓ Originally formulated for DC-8 flap track fairings



Rev: 20066G
10-08-2021

 For more information contact us :
zipchem@addevmaterials.com

 Part of 

ZC-460***Product description:*****MOLY DRI-LUBE****APPLICATIONS:**

- ✓ Used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser pre-cooler duct seal lubrication

PHYSICAL PROPERTIES:

- ▶ **Average Particle Size:** MoS₂ (0.4 Microns)
- ▶ **Boundary Lubrication:** 660°F (350°C)
- ▶ **Coefficient of Friction:** .23 (Static)
- ▶ **Color:** Gray
- ▶ **Service Temp:** 390°F (200°C)

AVAILABLE PACK SIZES:

- ▶ Aerosol-002061]
- ▶ Gallons-002318]
- ▶ Special Packaging Upon Request]