

### D-5261NS



#### Product description:

### CLEANER LUBRICANT PENETRANT

#### FEATURES:

- ▶ A special formulation of oil formulation that conforms to Mil-PRF-7870D.

#### KEY BENEFITS:

- ▶ Provides superior resistance to oxidation
- ▶ Ensures that parts, especially metals, do not rust
- ▶ Limits galvanic corrosion from occurring, especially on dissimilar metal assemblies
- ▶ **D-5261NS** can be used over temperatures from -65°F (-54°C) to 250°F (121°C)
- ▶ Prevents corrosion on metals

#### SPECS:

- MIL-PRF-7870D (Oil used in **D-5261NS**)

#### APPLICATIONS:

- ✓ Available in bulk as **ZC-5261**



- ▶ A very effective cleaner and penetrating lubricant
- ▶ Penetrates tight parts (ie: heart strands of cables) and deposits a rust preventive lubricating film

**D-5261NS***Product description:***CLEANER LUBRICANT PENETRANT****APPLICATIONS:**

- ✓ **D-5261NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the technical data sheet for more information.
- ✓ Use on aircraft flight controls, engine and landing gear cables, pulleys, pressure seals, cargo hoist cables, cargo restraining system components, door interlock actuating mechanisms, slide mechanisms, hinges, and static joints

**PHYSICAL PROPERTIES:**

- ▶ **Evaporation Rate:** Faster than ether
- ▶ **Flash Point of Oil:** 300°F (149°C)
- ▶ **Specific Gravity (H<sub>2</sub>O=1):** 0.88
- ▶ **Temperature Range:** -65°F (-54°C) to 250°F (121°C)
- ▶ **Vapor Density:** Heavier than air
- ▶ **Viscosity @ 100°F (38°C):** Min. 10 cst.

**AVAILABLE PACK SIZES:**

- ▶ Case of 12 of 12 fl oz (355 ml) Aerosols-002056
- ▶ Case of 4 each Gallon (4 each of 3.8L) Cans-009425
- ▶ 5 Gallon (18.9L) Pail-002138
- ▶ Special Packaging Upon Request