

D-5665NS



Product description: **CONTACT CLEANER**

FEATURES:

- ▶ A non-ozone depleting formulation (no CFC's or HCFC's)

KEY BENEFITS:

- ▶ Safe for use on plastics
 - ▶ Very low surface residue
 - ▶ Low toxicity levels
 - ▶ Very effective in solubilizing a select range of soils and surface contaminants
 - ▶ Non-flammable (Ingredients)
 - ▶ VOC exempt (Ingredients)
 - ▶ Highly Efficient (Ingredients)
 - ▶ Low GWP
 - ▶ Low odor
 - ▶ Fast evaporation
 - ▶ Exhibits an extremely low solubility of moisture
- ▶ The high density of **D-5665NS** coupled with a low viscosity and low surface tension, results in it coating surfaces evenly and penetrating into complex geometries
 - ▶ The complete evacuation of contents with steady and reliable pressure is guaranteed even if the aerosol can is inverted
 - ▶ Low surface tension



Rev: 29096L
10-29-2021

D-5665NS



Product description:

CONTACT CLEANER

KEY BENEFITS:

- ▶ **D-5665NS** can be sprayed directly into problem areas to loosen, lift, and flush away light deposits of undesirable oils, greases, and oxide build-up

SPECS:

- Boeing BAC 5402
- Boeing BAC 5750
- MIL-STD-1330D

APPLICATIONS:

- ✓ Ideal for use on electronic components and energized circuits
- ✓ Use for precision cleaning and the testing of oxygen systems
- ✓ Use in applications, such as the displacement drying and cleaning of water sensitive components
- ✓ **D-5665NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Available in bulk as **ZC-665**
- ✓ For heavier duty degreasing applications, evaluate **Sur-Prep® 5672**.

PHYSICAL PROPERTIES:

- ▶ **Appearance:** Clear / Colorless
- ▶ **Boiling Point (°C):** 60
- ▶ **Composite Vapor Pressure (minus exempt solvents):** 0 mm of Hg
- ▶ **Critical Temperature:** 195.3°C (383.5°F)

D-5665NS



Product description: **CONTACT CLEANER**

PHYSICAL PROPERTIES:

- ▶ **Dielectric Strength Constant 100Hz - 10MHz:** 7.39
 - ▶ **Flash Point (°C):** None
 - ▶ **Liquid Density (g/ml):** 1.50
 - ▶ **Low Heat of Vaporization (cal/g):** 0.28
 - ▶ **Non-Volatile Residue:** 1.0 ppm maximum
 - ▶ **Ozone Depletion:** 0.00
 - ▶ **Surface Tension (Dynes/cm):** 13.60
 - ▶ **Typical Dielectric Strength @ 25°C (77°F) (0.1 in gap):** 28 KV⁹
 - ▶ **Vapor Pressure @ 23°C (73°F) (including exempt solvents):** 195 mm of Hg
 - ▶ **Viscosity (cps):** 0.61
 - ▶ **VOC:** None
 - ▶ **Volume Resistivity @ 25°C (77°F), ohm-cm:** 3.29 x 10
-

AVAILABLE PACK SIZES:

- ▶ 12 fl oz (355 ml) Aerosol-002074
- ▶ 5 Gallon (18.9L) Pail-002158
- ▶ 55 Gallon (208L) Drum-007571
- ▶ Special Packaging Upon Request