

Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

ZC-440



Product description:
FLUOROCARBON DRY LUBRICANT

FEATURES:

- ▶ A fluorocarbon telomer that is chemically similar to the PTFE-fluorocarbon resin

KEY BENEFITS:

- ▶ Does not run or stain
 - ▶ Excellent dry film lubricant for wood, plastic, rubber, paper, and metal
 - ▶ Prevents corrosion on metal substrates and provides a lubricating surface for them
 - ▶ Excellent anti-stick properties
 - ▶ Non-flammable
 - ▶ Non-conductive and chemically inert
 - ▶ Withstands temperatures up to 500°F (260°C) continuously
 - ▶ Finds many uses throughout the aircraft
- ▶ Withstands temperatures from the cryogenic range up to 240°F (116°C)
 - ▶ Provides substrate with highest adhesion possible while providing lubricating properties or a good release
 - ▶ Effective release agent for epoxies, polyurethanes, etc



Rev: 29129C
11-30-2021

 For more information contact us :
zipchem@addevmaterials.com

 Part of 

ZC-440*Product description:***FLUOROCARBON DRY LUBRICANT****APPLICATIONS:**

- ✓ Aerosol application available as **D-5440NS**
- ✓ The **ZC-440** fluorocarbon is designed primarily for use as a dry film lubricant or mold release where it is applied to a cold or warm surface (less than 240°F (116°C))
- ✓ Applied on slat tracks to prevent corrosion and provide lubrication without the buildup of debris that is typically found if greases and oils are used
- ✓ Agitate constantly if using this material in bulk form

PHYSICAL PROPERTIES:

- ▶ **Density:** 2.16 grams/cc
- ▶ **Melting Point:** 572°F (300°C)
- ▶ **Softening Point:** 510°F (265°C)

AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002060
- ▶ Case of 12 each Quart (946 ml)-009660
- ▶ Case of 4 each Gallon (4 each of 3.8L) Cans-007070
- ▶ 5 Gallon (18.9L) Pail-007071
- ▶ 55 Gallon (208L) Drum-007072
- ▶ Special Packaging Upon Request