

### D-5100NS



#### *Product description:* **PURE SILICONE LUBRICANT**

#### **FEATURES:**

- ▶ A high quality lubricant and anti-stick agent
- ▶ A colorless and pure silicone fluid
- ▶ An odorless material

#### **KEY BENEFITS:**

- ▶ Does not stain fabrics
- ▶ Does not harm metals, plastics, or painted surfaces
- ▶ Prevents door locks and rubber weather stripping from freezing
- ▶ Reduces friction on iron faces and work surfaces where cloth is handled
- ▶ Retains excellent electrical properties and high temperature oxidation resistance that is inherent in silicones
- ▶ Can be used as a release agent for the molding of plastics and for the manufacturing of rubber and paper
- ▶ Lubricates dissimilar metals, plastics, and plastic-metal combinations
- ▶ **D-5100NS** has a temperature range from -60°F to 600°F (-51°C to 315°C)
- ▶ Can be used as an anti-stick agent for heat sealing equipment, packaging and gluing equipment, conveyors, and food processing equipment



Rev: 20062B  
04-06-2022

### D-5100NS



## Product description: PURE SILICONE LUBRICANT

### SPECS:

- VV-D-1078 (Silicone used in **D-5100NS**)
- NSN: 9150-00-269-8249 (16 fl oz (473 ml) Aerosol)

### APPLICATIONS:

- ✓ **D-5100NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.

### PHYSICAL PROPERTIES:

The following physical properties are based on the silicone fluid used in **D-5100NS**

- ▶ **Dielectric Constant:** 2.65 to 2.77 at 25°F (-4°C)
- ▶ **Dielectric Strength:** 240 to 360 Volts Per Mil
- ▶ **Pour Point:** 58°F (14°C)
- ▶ **Specific Gravity 25°C/25°C (77°F/77°F):** 0.8
- ▶ **Surface Tension:** 21 Dynes/Centimeter

### AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002055 →
- ▶ Special Packaging Upon Request

