

Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

D-5922NS



Product description: **MICROGEL/SYNTHETIC MULTI-PURPOSE GREASE**

FEATURES:

- ▶ The aerosolized form of Aeroshell® 22 Grease, a versatile and multi-purpose microgel that is a thickened, synthetic and hydrocarbon oil

KEY BENEFITS:

- ▶ Superior anti-wear properties, load carrying capacity, and water resistance
- ▶ A useful temperature range of -85°F to 400°F (-65°C to 204°C)
- ▶ Heavily fortified against oxidation
- ▶ A corrosion inhibited product
- ▶ The **D-5922NS** aerosol offers ease of application for hard to reach areas

APPLICATIONS:

- ✓ **D-5922NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.



Rev: 29096K
11-30-2022

 For more information contact us :
zipchem@addevmaterials.com



D-5922NS

Product description:
MICROGEL/SYNTHETIC MULTI-PURPOSE GREASE

APPLICATIONS:

- ✓ **Aircraft:** Useful for engine accessories, airframe lubrication, and general anti-friction bearings which operate at high speeds in high and low temperatures
- ✓ Use **D-5922NS** for long retention and high water resistance environments

PHYSICAL PROPERTIES:

- ▶ **Color:** Amber
- ▶ **Grease Drop Point:** 500+
- ▶ **Operating Temperatures:** -85°F to 400°F (-65°C to 204°C)
- ▶ **Penetration of Grease (Worked):** 295
- ▶ **Water Resistance % W:** 1.3

AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002082
- ▶ Special Packaging Upon Request

D-5922NS contains Shell Oil Co. Aeroshell® 22 Grease. The Aeroshell® 22 Grease microgel is a Shell Oil Co. registered trademark.