

D-5100NS



Product description:

A FUNCTIONAL SILICONE FLUID

FEATURES:

- A high quality lubricant and anti-stick agent
- A colorless and pure silicone fluid
- An odorless material

KEY BENEFITS:

- Does not harm metals, plastics, or painted surfaces
- Prevents door locks and rubber weather stripping from freezing
- Reduces friction on iron faces and work surfaces where cloth is handled
- Retains excellent electrical properties and high temperature oxidation resistance that is inherent in silicones
- Lubricates dissimilar metals, plastics, and plastic-metal combinations



- Can be used as a release agent for the molding of plastics and for the manufacturing of rubber and paper
- D-5100NS has a temperature range from -60°F to 600°F (-51°C to 315°C)
- Can be used as an anti-stick agent for heat sealing equipment, packaging and gluing equipment, conveyors, and food processing equipment
- Does not stain fabrics

Rev: 20063C 02-08-2023





D-5100NS



Product description:

A FUNCTIONAL SILICONE FLUID

SPECS:

- VV-D-1078 (Silicone used in **D-5100NS**)
- NSN: 9150-00-269-8249 (16 fl oz (473 ml) Aerosol)

APPLICATIONS:

✓ **D-5100NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.

PHYSICAL PROPERTIES:

The following physical properties are based on the silicone fluid used in D-5100NS

- Dielectric Constant: 2.65 to 2.77 at 25°F (-4°C)
- ▶ **Dielectric Strength:** 240 to 360 Volts Per Mil
- **Pour Point:** 58°F (14°C)
- ► Specific Gravity 25°C/25°C (77°F/77°F): 0.8
- Surface Tension: 21 Dynes/Centimeter

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002055
- Special Packaging Upon Request



