

ZC-035



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

FEATURES:

- A heat resistant corrosion preventive
- Provides a firm and waxy coating

KEY BENEFITS:

- ZC-035 is formulated to provide long term protection against corrosion
- ► The ZC-035 coating withstands continuous temperatures up to 350°F (177°C), with a short term exposure up to 430°F (221°C)
- The ZC-035 coating contains excellent moisture displacing qualities and adhesion capabilities
- Free of chromates
- Free from heavy metals

ZC-035 A heat resistant corrosion preventive FOR HIGH TEMPERATURE AREAS Net Contents: 1 Gallon

- ► The ZC-035 coating provides over 1300 hours of protection on steel in a salt fog environment
- The ZC-035 coating provides superior dampening for metals
- The ZC-035 coating contains properties to neutralize acid
- Low toxicity

SPECS:

Boeing QPL for DPM 5217

Rev: 20068I 07-03-2023







ZC-035



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

APPLICATIONS:

- ✓ A dry film thickness of 1.0 mil (25 microns) provides a transparent coating
- √ Aerosol application available as D-5035NS
- ✓ Firm and waxy coating of ZC-035 can be easily removed with petroleum solvents

PHYSICAL PROPERTIES:

- Evaporation Rate: Faster Than Ether
- Fungal Growth per Fed-STD-810 Method 508.7: 0 (No Microbial Growth)
- ► Material V.O.C.: 583 g/L (4.8 lbs/gal)
- ► Melt Point: 550°F (28°C)
- Specific Gravity: 0.8
- Vapor Density: Heavier Than Air

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002052
- Case of 4 each Gallon (4 each of 3.8 L) Cans-002115









ZC-035



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

AVAILABLE PACK SIZES:

- ► 5 Gallon (18.9 L) Pail-002116
- ▶ 55 Gallon (208 L) Drum-002117
- Special Packaging Upon Request

