

LUBRICANTS & LUBRICATING COMPOUNDS

D-5480NS



Product description: GRAPHITE DRY LUBRICANT

FEATURES:

- A colloidal graphite dispersion in a thermoplastic resin
- The aerosol application of the D-5480NS Graphite produces an extremely tenacious dry film of fine particle size graphite on the surface to be lubricated
- Dries rapidly at room temperature

KEY BENEFITS:

- Does not contain grease, wax or silicone
- Forms a stable film that can withstand continuous temperatures of 400°F (204°C) to 850°F (454°C) for limited time periods
- D-5480NS has strong properties for plating non-conductors

SPECS:

- ASTM F945
- UAL LUB 4500-35C

APPLICATIONS:

✓ Bulk application available as ZC-480

Rev: 29096E 08-18-2023







LUBRICANTS & LUBRICATING COMPOUNDS

ero-Lu

D-5480NS



Product description: GRAPHITE DRY LUBRICANT

APPLICATIONS:

- ✓ D-5480NS can be used in conjunction with the Formit[®] extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the Formit[®] technical data sheet for more information.
- ✓ Apply on:
 - Air Conditioning and Heating Duct Controls
 - Internal Combustion Engines
 - Bearings
 - Conveyer Components
 - Dyes
 - O-Rings
 - Pistons
 - Gears

- Hoists
- Locks
- Chains
- Non-Conductor Plating
- Flatleaf Springs
- Gaskets
- Plating Printing Circuits
- •Tools

PHYSICAL PROPERTIES:

- Color: Black
- Density: 7.5 lbs / gal (899 g/L)
- Friction Coefficient: 0.19 (static)
- Service Temperature: 400°F (204°C)
- Intermittent Temperature: 850°F (454°C)





Aero-Luberter

LUBRICANTS & LUBRICATING COMPOUNDS

D-5480NS



Product description: GRAPHITE DRY LUBRICANT

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002062
- Case of 4 each Gallon (4 each of 3.8L) Cans-100437
- 5 Gallon (18.9L) Pail-100438
- Special Packaging Upon Request



