

# Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

## ZC-460



*Product description:*

### **MOLY DRI-LUBE**

#### **FEATURES:**

- ▶ A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- ▶ Contains a dry film
- ▶ An extreme pressure lube

#### **KEY BENEFITS:**

- ▶ Excellent high temperature stability
- ▶ Good surface adhesion
- ▶ Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- ▶ Contains a fast drying formula
- ▶ Yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)



#### **SPECS:**

- GE Aviation GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC

#### **APPLICATIONS:**

- ✓ Aerosol application available as **D-5460NS**
- ✓ Originally formulated for DC-8 flap track fairings

Rev: 200671  
09-25-2023

 For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)

 Part of 

**ZC-460**

## *Product description:*

### **MOLY DRI-LUBE**

#### **APPLICATIONS:**

- ✓ Used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser pre-cooler duct seal lubrication

#### **PHYSICAL PROPERTIES:**

- ▶ **Average Particle Size:** MoS<sub>2</sub> (0.4 Microns (0.01 Mils))
- ▶ **Coefficient of Friction:** .23 (Static)
- ▶ **Color:** Gray
- ▶ **Service Temp:** 390°F (200°C)

#### **AVAILABLE PACK SIZES:**

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002061
- ▶ Case of 4 each Gallon (4 each of 3.8L) Cans-002318
- ▶ Special Packaging Upon Request