

# Cor-Ban®

CORROSION INHIBITING COMPOUNDS

## NOXIT® 86



### Product description: "FOGGING" CORROSION INHIBITING COMPOUND

#### FEATURES:

- ▶ A heavy duty, water displacing, non-drying, thin film, corrosion preventive compound

#### KEY BENEFITS:

- ▶ Contains no ozone depleting chemicals
- ▶ Contacts corrosion in all areas of the airplane
- ▶ Integral part of the corrosion control program
- ▶ Does not harm most paints, plastics, or insulation
- ▶ Free of chromates
- ▶ Free from heavy metals
- ▶ Low toxicity
- ▶ Prevents corrosion
- ▶ Provides light lubrication
- ▶ Useful for initial protection during shipment and storage as well as in-service treatment of critical areas
- ▶ Protects cables and interior and exterior aircraft surfaces

#### SPECS:

- Class 2, Grade 134A
- NSN: 8030-01-524-0114
- QPL for Mil-PRF-81309H Type II & III



 For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)



Part of



MATERIALS

Rev: 290731  
10-19-2023

### NOXIT® 86



*Product description:*  
**"FOGGING" CORROSION  
INHIBITING COMPOUND**

#### APPLICATIONS:

- ✓ When used in conjunction with the **Formit®-18-90-FOG** or **Formit® -18-STD-FOG**, the **Noxit® 86** aerosol can form a corrosion inhibiting fog which will coat hard to reach areas
- ✓ One aerosol will cover about 70ft<sup>2</sup> (6.5 m<sup>2</sup>) at the recommended thickness
- ✓ Use on highly critical metal surfaces and cables
- ✓ Suitable for service use due to its complete miscibility with lubricating oil and ease of application

#### PHYSICAL PROPERTIES:

- ▶ **Boiling Range:** -22°F to 375°F (-30°C to 190°C)
- ▶ **Evaporation Rate:** Faster than ether
- ▶ **Flame Extension:** Flammable
- ▶ **Specific Gravity (H<sub>2</sub>O=1):** 1.1
- ▶ **Vapor Density:** Heavier than air

#### AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 mL) Aerosols-002049
- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-008997
- ▶ 5 Gallon (18.9 Liter) Pail-008998
- ▶ 55 Gallon (208 Liter) Drum-008999
- ▶ Special Packaging Upon Request