

ZC-460



Page 1 of 2

Product description:

MOLY DRI-LUBE

FEATURES:

- ▶ A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- ▶ Contains a dry film
- ▶ An extreme pressure lube

KEY BENEFITS:

- ▶ Excellent high temperature stability
- ▶ Good surface adhesion
- ▶ Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- ▶ Contains a fast drying formula
- ▶ Yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)

SPECS:

- GE Aviation GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC

APPLICATIONS:

- ✓ Aerosol application available as **D-5460NS**
- ✓ Originally formulated for DC-8 flap track fairings



Applications Continued On The Next Page

Rev: 20068K
07-08-2024

ZC-460

Page 2 of 2

*Product description:***MOLY DRI-LUBE****APPLICATIONS CONTINUED FROM PAGE 1:**

- ✓ Used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser pre-cooler duct seal lubrication

PHYSICAL PROPERTIES:

- ▶ **Average Particle Size:** MoS₂ (0.4 Microns (0.01 Mils))
- ▶ **Coefficient of Friction:** .23 (Static)
- ▶ **Color:** Gray
- ▶ **Service Temp:** 390°F (200°C)

AVAILABLE PACK SIZES:**D-5460NS**

- ▶ Case of 12 of 16 fl oz (473 mL) Aerosols-002061

ZC-460

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-002318
- ▶ Special Packaging Upon Request