

ZC-029



Page 1 of 3

Product description: **CORROSION INHIBITING COMPOUND**

FEATURES:

- ▶ A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- ▶ Non-tacky with a light amber tint

KEY BENEFITS:

- ▶ > 1500 hours salt spray on aluminum (Al)
- ▶ Fast drying and non-tacky
- ▶ Non-cracking and flaking up to -40°F (-40°C)
- ▶ Free of chromates
- ▶ Free from heavy metals
- ▶ Low toxicity
- ▶ Has a detectable film
- ▶ Solvent removable
- ▶ Very low dry weight film
- ▶ High Solids > 51%

SPECS:

- Boeing BMS 3-29
- Boeing DMS 2150 Type 1 & Type 2



ZC-029



Page 2 of 3

Product description:
**CORROSION INHIBITING
COMPOUND**

APPLICATIONS:

- ✓ Apply via airless or air-operated spray equipment
 - ✓ Apply at 2-3 mils (51 to 76 microns) of wet thickness. This wet thickness can be measured with Zip-Chem®'s **Wet Film Thickness Gauge**.
 - ✓ Aerosol application available as **D-5029NS**
 - ✓ Use on high profile aircraft substrates
-

PHYSICAL PROPERTIES:

- ▶ **Color:** Transparent Amber
- ▶ **Drying Time:** <12 hours
- ▶ **Flash Point:** 122°F (50°C)
- ▶ **Non-Volatiles:** 51% min.
- ▶ **Specific Gravity:** 0.89
- ▶ **Viscosity:** 140 cps.
- ▶ **Water Displacement:** 0% Rust

ZC-029



Page 3 of 3

Product description:

CORROSION INHIBITING COMPOUND

AVAILABLE PACK SIZES:

D-5029NS

- ▶ Case of 12 of 16 fl oz (473 mL) Aerosols-002050

ZC-029

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-009422
- ▶ 5 Gallon (18.9 Liter) Pail-002109
- ▶ 55 Gallon (208 Liter) Drum-002110
- ▶ Special Packaging Upon Request

Wet Film Thickness Gauge

- ▶ 100266



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS