



## AIRCRAFT CLEANERS & DISINFECTANTS

### ZIP-STRIP™ 125M



Page 1 of 3

### Product description: WATER RINSEABLE CIC REMOVER

#### FEATURES:

- ▶ A fast acting neutral pH CIC remover

#### KEY BENEFITS:

- ▶ Contains biodegradable components
- ▶ Removes wet, waxy, and/or dry film corrosion inhibiting compounds (CIC's)
- ▶ Contains water rinseable material
- ▶ Effective on aviation soils, such as MoS<sub>2</sub> grease, hydraulic fluid, wax, and carbon deposits
- ▶ Very effective after a short dwell time



#### SPECS:

- Airbus AIMS 09-00-002
- Boeing BSS 7432
- Boeing D6-17487
- NSN: 6850-01-707-8887 (16 fl oz (473 mL) Aerosol)
- NSN: 6850-01-695-8514 (5 Gallon (18.9 Liter) Pail)
- T.O. 1C-130A-23
- T.O. 1C-130J-23

#### APPLICATIONS:

- ✓ Zip-Strip™ 125M can be applied by aerosol, airless, air-assist, dipping, or brushing
- ✓ Zip-Strip™ 125M can be used on all access panel fasteners
- ✓ The material should be applied at a thickness of 2 to 7 mils (51-178 microns), depending on the thickness and age of the material to be removed
- ✓ Zip-Strip™ 125M should be stored at 40 to 100°F (4.4° - 37.8°C) and away from direct sunlight.

Rev: 29316D  
04-08-2025



## ZIP-STRIP™ 125M



### *Product description:* **WATER RINSEABLE CIC REMOVER**

#### **APPLICATIONS CONTINUED FROM PAGE 1:**

- ✓ Allow material to dwell for 5-10 minutes (10-20 minutes for heavy duty removal) and then pressure spray or rinse off.
- ✓ Do not allow material to dry on the surface. If drying commences, apply a light film of additional **Zip-Strip™ 125M** and rinse off.
- ✓ The **Zip-Strip™ 125M aerosol** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be cleaned. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Handle effluent accordingly because the contaminants that **Zip-Strip™ 125M** removes may not be biodegradable

#### **PHYSICAL PROPERTIES:**

- ▶ **Appearance:** Clear liquid
- ▶ **Bulk Density:** 7.0 lbs per gallon (839 grams per liter)
- ▶ **Composite Vapor Pressure:** 0.5 mm of Hg @ 25°C (77°F)
- ▶ **Flash Point:** 127°F (53°C) PMCC
- ▶ **Odor:** Solvent Odor
- ▶ **Specific Gravity:** 0.84
- ▶ **Viscosity:** 200 cps.
- ▶ **VOC Grams / Liter:** 253 grams/liter (2.1 lbs/gallon)
- ▶ **Volatiles:** 87% by weight



## AIRCRAFT CLEANERS & DISINFECTANTS

### ZIP-STRIP™ 125M



Page 3 of 3

### *Product description:* **WATER RINSEABLE CIC REMOVER**

#### AVAILABLE PACK SIZES:

##### Zip-Strip™ 125M

- ▶ 16 fl oz (473 mL) Aerosol-102614
- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-102608
- ▶ 5 Gallon (18.9 Liter) Pails-102609
- ▶ 55 Gallon (208 Liter) Drums-102610
- ▶ Special Packaging Upon Request

##### Formit®

- ▶ 12 Assemblies Per Package
- ▶ **Formit® Sample Pack** with 3 each of  
**Formit®-18-F,**  
**Formit®-18-180,**  
**Formit®-18-360,**  
and **Formit®-18 STD-Fog-100107**

