

NOXIT® 86



Product description:

"FOGGING" CORROSION INHIBITING COMPOUND

FEATURES:

A heavy duty, water displacing, non-drying, thin film, corrosion preventive compound

KEY BENEFITS:

- Contains no ozone depleting chemicals
- Contacts corrosion in all areas of the airplane
- Integral part of the corrosion control program
- Does not harm most paints, plastics, or insulation
- Free of chromates
- Free from heavy metals

SPECS:

- Class 2, Grade 134A
- NSN: 8030-01-524-0114

Page 1 of 3



- Low toxicity
- Prevents corrosion
- **Provides light lubrication**
- Useful for initial protection during shipment and storage as well as inservice treatment of critical areas
- Protects cables and interior and exterior aircraft surfaces

QPL for Mil-PRF-81309H Type II & III

Rev: 29074J 05-05-2025







NOXIT® 86



Page 2 of 3

Product description:

"FOGGING" CORROSION INHIBITING COMPOUND

APPLICATIONS:

- ✓ When used in conjunction with the Formit®-18-90-FOG or Formit® -18-STD-FOG, the Noxit® 86 aerosol can form a corrosion inhibiting fog which will coat hard to reach areas
- ✓ One aerosol will cover about 70ft² (6.5 m²) at the recommended thickness
- ✓ Use on highly critical metal surfaces and cables
- ✓ Suitable for service use due to its complete miscibility with lubricating oil and ease of application
- ✓ Store Noxit® 86 at 40°F 100°F (4.4°C 37.8°C) in the original unopened containers

PHYSICAL PROPERTIES:

▶ Boiling Range: -22°F to 375°F (-30°C to 190°C)

Evaporation Rate: Faster than ether

Flame Extension: FlammableSpecific Gravity (H₂O=1): 1.1

Vapor Density: Heavier than air





NOXIT® 86



Page 3 of 3

Product description:

"FOGGING" CORROSION INHIBITING COMPOUND

AVAILABLE PACK SIZES:

Noxit® 86

- Case of 12 of 16 fl oz (473 mL) Aerosols-002049
- Case of 4 each Gallon (4 each of 3.8 Liter) Cans-008997
- 5 Gallon (18.9 Liter) Pail-008998
- 55 Gallon (208 Liter) Drum-008999
- Special Packaging Upon Request

Formit[®]

- ▶ 12 Assemblies Per Package —
- Formit® Sample Pack with 3 each of Formit®-18-F,

Formit®-18-180, —

Formit®-18-360,





