

ZC-035



Page 1 of 3

Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

FEATURES:

- ▶ A heat resistant corrosion preventive
- ▶ Provides a firm and waxy coating

KEY BENEFITS:

- ▶ **ZC-035** is formulated to provide long term protection against corrosion
- ▶ The **ZC-035** coating withstands continuous temperatures up to 350°F (177°C), with a short term exposure up to 430°F (221°C)
- ▶ The **ZC-035** coating contains excellent moisture displacing qualities and adhesion capabilities
- ▶ Free of chromates
- ▶ Free from heavy metals
- ▶ The **ZC-035** coating provides over 1300 hours of protection on steel in a salt fog environment
- ▶ The **ZC-035** coating provides superior dampening for metals
- ▶ The **ZC-035** coating contains properties to neutralize acid
- ▶ Low toxicity



SPECS:

- Boeing QPL for DPM 5217

Rev: 20070J
07-22-2025

ZC-035



Page 2 of 3

Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

APPLICATIONS:

- ✓ A dry film thickness of 1.0 mil (25 microns) provides a transparent coating
- ✓ Aerosol application available as **D-5035NS**
- ✓ Firm and waxy coating of **ZC-035** can be easily removed with petroleum solvents
- ✓ Store **ZC-035** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers

PHYSICAL PROPERTIES:

- ▶ **Evaporation Rate:** Faster Than Ether
- ▶ **Fungal Growth per Fed-STD-810 Method 508.7:** 0 (No Microbial Growth)
- ▶ **Material V.O.C.:** 583 grams / Liter (4.8 lbs / gallon)
- ▶ **Melt Point:** 550°F (28°C)
- ▶ **Specific Gravity:** 0.8
- ▶ **Vapor Density:** Heavier Than Air



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS

ZC-035



Page 3 of 3

Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

AVAILABLE PACK SIZES:

D-5035NS

- ▶ Case of 12 of 16 fl oz (473 mL) Aerosols-002052



ZC-035

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-002115
- ▶ 5 Gallon (18.9 Liter) Pail-002116
- ▶ 55 Gallon (208 Liter) Drum-002117
- ▶ Special Packaging Upon Request



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS