

D-5933NS



Page 1 of 3

Product description: **AEROSOLIZED GREASE**

FEATURES:

- ▶ Contains Shell Oil Company's Aeroshell® Grease 33, a multipurpose airframe grease
- ▶ Made with a synthetic base oil and a lithium complex thickener

KEY BENEFITS:

- ▶ Provides enhanced corrosion resistance and load-carrying capacity
- ▶ Reduces expense of wasting lubricant
- ▶ **D-5933NS** contains a useful temperature range of -100° F (-73°C) to +250° F (+121°C)
- ▶ Saves valuable time and labor
- ▶ Applies a clean and uncontaminated layer of grease where it is needed
- ▶ Non-toxic

SPECS:

- Boeing QPL for BMS 3-33C Type 2
- MIL-PRF-23827C Ty 1 (Aeroshell® 33 grease)



Rev: 29068H
11-13-2025

D-5933NS



Page 2 of 3

Product description:
AEROSOLIZED GREASE

APPLICATIONS:

- ✓ **D-5933NS** should not be used to replace lubrication that was achieved by grease gun application through zerk fittings
- ✓ Can be used in combination with a snorkel
- ✓ In use, the non-toxic, non-flammable propellants vaporize so that the lubricant is the only liquid that is left behind.
- ✓ Use where drawings or maintenance manuals allow the use of hand or brush application of bulk grease
- ✓ **D-5933NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Use as a replacement for molybdenum disulfide in problem areas like the tailing edge flaps
- ✓ Other applications include the general airframe lubricant, highly loaded gears, actuator screw mechanisms, instruments, and all sliding and wiping surfaces with moisture entrapment problems
- ✓ Store **D-5933NS** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers away from sunlight



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



LUBRICANTS & LUBRICATING COMPOUNDS

D-5933NS



Page 3 of 3

Product description: **AEROSOLIZED GREASE**

PHYSICAL PROPERTIES:

- **Color:** Green
- **Mean Hertz Load, Kg:** 60
- **Melting Point:** None
- **Grease Operating Temperature:** -100 to +250°F (-73°C to 121°C)
- **Spray Application Temperature Range:** 20° F to 120° F (-7°C to 49°C)
- **Water Resistance, % w Loss@ 175°F (79°C):** <6

AVAILABLE PACK SIZES:

D-5933NS

- 16 fl oz (473 mL) Aerosol-008431

Formit®

- 12 Assemblies Per Package
- **Formit® Sample Pack** with 3 each of
Formit®-18-F,
Formit®-18-180,
Formit®-18-360,
and **Formit®-18 STD-Fog-100107**



Aeroshell® Grease 33 is a Shell Oil Co. registered trademark.



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS