



Page 1 of 5

Product description: CORROSION INHIBITING COMPOUND

FEATURES:

- A long lasting, water displacing, corrosion inhibiting compound
- Cor-Ban® 22 formula is based on the Cor-Ban® 27L CIC
- A soft and self healing finished coating

KEY BENEFITS:

- No cracking or flaking to -60°F (-51°C)
- Cor-Ban® 22 can be applied to corroded areas to prevent further corrosion from occurring
- Provides additional barrier protection for corrosion prone internal steel bores of horizontal pivot shafts and landing gear bogies
- Free of chromates and heavy metals
- Low toxicity
- Film is detectable and non-sagging
- Solvent removable
- A military approved CIC for stopping corrosion on pre-corroded metal parts

Rev: 20066J 12-12-2025











Page 2 of 5

Product description:

CORROSION INHIBITING COMPOUND

KEY BENEFITS (CONTINUED FROM PAGE 1):

- Highly penetrating formula delivers the corrosion protection of Cor-Ban® 27L into faying surfaces
- Preferred CIC for routine maintenance
- > 4000 hours of salt spray

SPECS:

- Boeing BMS 3-23 (Meets requirements)
- NSN 8030-01-523-4290 (16 fl oz (473 mL) Aerosol)
- NSN 8030-01-531-7352 (5 Gallon (18.9 Liter) Pail)
- T.O. 1C-130A-23
- T.O. 1C-5A-23
- T.O. 1C-130J-23
- T.O. 1C-130J-2-00GV-00-1

APPLICATIONS:

- ✓ Apply by conventional airless, air-operated spray equipment, or by aerosol
- ✓ Cor-Ban® 22 can be applied over pre-existing corrosion
- ✓ The coating can be applied as thin as 1 mil (25 microns) film thickness to achieve the desired corrosion protection
- ✓ The Cor-Ban® 22 aerosol can be used in conjunction with the Formit® extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the Formit® technical data sheet for more information.
- ✓ All properties represented were achieved with a wet film thickness of 1.0 mils (25 microns). This wet film thickness can be measured with **Zip-Chem®** 's **Wet Film Thickness Gauge**.
- ✓ One aerosol can covers approximately 90 ft² (8.3 m²)
- ✓ Paste application of Cor-Ban® 22 is available as Cor-Ban® 27L
- ✓ Apply Cor-Ban® 22 on landing gear equipment and hardware that is not primed or top coated







Page 3 of 5

Product description:

CORROSION INHIBITING COMPOUND

APPLICATIONS (CONTINUED FROM PAGE 2):

✓ Store **Cor-Ban® 22** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect **Cor-Ban® 22** from direct sunlight.

PHYSICAL PROPERTIES:

- ► Color: reddish-brown
- Compatibility Cd, Mg, AI: Pass
- Corrosion Resistance ASTM B-117: >4000 hours on Steel
- ► Flash Point: 105°F (40°C)
- Fungal Growth per Fed-STD-810 Method 508.7: 0 (No Microbial Growth)
- Low Temp Flaking: Pass
- ► Material VOC: 538 grams/Liter (4.4 Lbs/Gal)
- Non-Volatiles: 33%
- ► Penetration: BMS 3-23F pass
- ▶ Shelf Life: 3 Years From Date Of Shipment If Properly Stored
- Solvent Type: Aliphatic
- Specific Gravity: 0.82







Page 4 of 5

Product description:

CORROSION INHIBITING COMPOUND

PHYSICAL PROPERTIES (CONTINUED FROM PAGE 3):

► Water Displacement: 0% Rust

Water Resistance: Pass

AVAILABLE PACK SIZES:

Cor-Ban® 22

- Case of 12 of 16 fl oz (473 mL) Aerosols-007047
- Case of 24 of 4 fl oz (118 mL) Aerosols-103734
- Case of 4 each Gallon (4 each of 3.8 Liter) Cans-009400
- ► 5 Gallon (18.9 Liter) Pail-007049
- 55 Gallon (208 Liter) Drum-007050
- Special Packaging Upon Request

Wet Film Thickness Gauge

100266







Page 5 of 5

Product description:

CORROSION INHIBITING COMPOUND

AVAILABLE PACK SIZES (CONTINUED FROM PAGE 4):

Cor-Ban® 27L

- Case of 12 of 5 fl oz (148 mL) Tubes-009402
- Case of 12 of 6 fl oz (177 mL) Semco® Cartridges-009403
- Case of 12 of 14 fl oz (414 mL) Grease Cartridges-009873
- Case of 12 each Quart (946 mL)-009405
- Case of 12 each Pint (473 mL) Cans-009404
- Case of 4 each Gallon (4 each of 3.8 Liter) Cans-009406
- ► 5 Gallon (18.9 Liter) Pail-002099
- Special Packaging Upon Request

Formit[®]

- ► 12 Assemblies Per Package
- Formit® Sample Pack with 3 each of Formit®-18-F,

Formit®-18-180, -

Formit®-18-360, and Formit®-18 STD-Fog-100107





