



LUBRICANTS & LUBRICATING COMPOUNDS

D-5100NS



Page 1 of 3

Product description:


A FUNCTIONAL SILICONE FLUID

FEATURES:

- ▶ A high quality lubricant and anti-stick agent
- ▶ A colorless and pure silicone fluid
- ▶ An odorless material

KEY BENEFITS:

- ▶ Does not harm metals, plastics, or painted surfaces
- ▶ Prevents door locks and rubber weather stripping from freezing
- ▶ Reduces friction on iron faces and work surfaces where cloth is handled
- ▶ Retains excellent electrical properties and high temperature oxidation resistance that is inherent in silicones
- ▶ Lubricates dissimilar metals, plastics, and plastic-metal combinations
- ▶ Can be used as a release agent for the molding of plastics and for the manufacturing of rubber and paper
- ▶ **D-5100NS** has a temperature range from -60°F to 600°F (-51°C to 315°C)
- ▶ Can be used as an anti-stick agent for heat sealing equipment, packaging and gluing equipment, conveyors, and food processing equipment
- ▶ Does not stain fabrics



Rev: 20065F
12-12-2025



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



D-5100NS



Page 2 of 3

Product description:

A FUNCTIONAL SILICONE FLUID

SPECS:

- NSN: 9150-00-269-8249 (16 fl oz (473 mL) Aerosol)

APPLICATIONS:

- ✓ **D-5100NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Store **D-5100NS** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect **D-5100NS** from direct sunlight.

PHYSICAL PROPERTIES:

The following physical properties are based on the silicone fluid used in **D-5100NS**

- ▶ **Dielectric Constant:** 2.65 to 2.77 at 25°F (-4°C)
- ▶ **Dielectric Strength:** 240 to 360 Volts Per Mil
- ▶ **Pour Point:** 58°F (14°C)
- ▶ **Specific Gravity 25°C/25°C (77°F/77°F):** 0.8
- ▶ **Surface Tension:** 21 Dynes/Centimeter

Note: The shelf life of **D-5100NS** is 3 years from the date of shipment if properly stored.



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS

D-5100NS



Page 3 of 3

Product description:

A FUNCTIONAL SILICONE FLUID


AVAILABLE PACK SIZES:

D-5100NS

- Case of 12 of 16 fl oz (473 mL) Aerosols-002055

Formit®

- 12 Assemblies Per Package
- **Formit® Sample Pack** with 3 each of
Formit®-18-F,
Formit®-18-180,
Formit®-18-360,
and **Formit®-18 STD-Fog-100107**



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS