

D-5907NS



Page 1 of 3

Product description:

MULTI-PURPOSE AIRCRAFT GREASE

FEATURES:

- ▶ Contains Shell Oil Company's Aeroshell® Grease 7, a multi-purpose grease

KEY BENEFITS:

- ▶ **D-5907NS** utilizes Aeroshell® 7 grease with a new environmentally acceptable non ozone depleting propellant system
- ▶ **D-5907NS** has a useful temperature range of -100°F (-73°C) to +300°F (149°C) with extremely high moisture resistance
- ▶ Aerosol permits application in hard to reach areas with advanced multi-purpose grease
- ▶ Saves time and labor
- ▶ Reduces the expense of wasting lubricant
- ▶ Always applies clean and uncontaminated grease where it is needed
- ▶ When **D-5907NS** is being used, propellants vaporize and leave only the lubricant that is needed



SPECS:

- Boeing QPL DPM 326-1
- Grease used in **D-5907NS**, Aeroshell® 7, conforms to GRE-4500-35C and Mil-G-23827

Rev: 29097N
12-12-2025



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



LUBRICANTS & LUBRICATING COMPOUNDS

D-5907NS



Page 2 of 3

Product description:

MULTI-PURPOSE AIRCRAFT GREASE

APPLICATIONS:

- ✓ **D-5907NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Suited for general aircraft lubrication
- ✓ Can be used as a replacement for molybdenum disulfide in problem areas like the tailing edge flaps.
- ✓ Other applications include:
 - The general airframe lubricant
 - Highly loaded gears
 - Actuator screw mechanisms
 - Instruments
 - All sliding and wiping surfaces that are subject to moisture entrapment problems
- ✓ Store **D-5907NS** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect **D-5907NS** from direct sunlight.

PHYSICAL PROPERTIES:

- ▶ **Melting Point:** None
- ▶ **Operating Temperature:** -100°F (-73°C) to +300°F (149°C)
- ▶ **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored
- ▶ **Typical Mean Hertz Load:** 60kg (132.2 lbs)
- ▶ **Viscosity @ 210°F (99°C):** 3.1 cs
- ▶ **Water Resistance Test Loss:** 0.80% at 38°C (100°F)



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

D-5907NS



Page 3 of 3

Product description:

MULTI-PURPOSE AIRCRAFT GREASE


AVAILABLE PACK SIZES:

D-5907NS

- Case of 12 of 16 fl oz (473 mL) Aerosols-002078

Formit®

- 12 Assemblies Per Package
- **Formit® Sample Pack** with 3 each of
Formit®-18-F,
Formit®-18-180,
Formit®-18-360,
and **Formit®-18 STD-Fog-100107**



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS