

ZIP-STRIP™ 125M



Product description:

WATER RINSEABLE CIC REMOVER

FEATURES:

A fast acting neutral pH CIC remover

KEY BENEFITS:


- Contains biodegradable components
- Removes wet, waxy, and/or dry film corrosion inhibiting compounds (CIC's)
- Contains water rinseable material
- Effective on aviation soils, such as MoS₂ grease, hydraulic fluid, wax, and carbon deposits
- Very effective after a short dwell time

SPECS:

- Airbus AIMS 09-00-002
- Boeing BSS 7432
- Boeing D6-17487

- NSN: 6850-01-707-8887 (16 fl oz (473 mL) Aerosol)
- NSN: 6850-01-695-8514 (5 Gallon (18.9 Liter) Pail)
- T.O. 1C-130A-23
- T.O. 1C-130J-23

Page 1 of 4



Zip-Strip 125 M

Rev: 29317E 12-12-2025





ZIP-STRIP™ 125M

Page 2 of 4

Product description: WATER RINSEABLE CIC REMOVER

APPLICATIONS:

- ✓ Zip-Strip™ 125M can be applied by aerosol, airless, air-assist, dipping, or brushing
- ✓ **Zip-Strip™ 125M** can be used on all access panel fasteners
- ✓ The material should be applied at a thickness of 2 to 7 mils (51-178 microns), depending on the thickness and age of the material to be removed
- ✓ **Zip-Strip[™] 125M** should be stored at 40°F to 100°F (4.4°C 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect **Zip-Strip[™] 125M** from direct sunlight.
- ✓ Allow material to dwell for 5-10 minutes (10-20 minutes for heavy duty removal) and then pressure spray or rinse off.
- ✓ Do not allow material to dry on the surface. If drying commences, apply a light film of additional **Zip-Strip™ 125M** and rinse off.
- ✓ The **Zip-Strip™ 125M aerosol** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be cleaned. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Handle effluent accordingly because the contaminants that Zip-Strip™ 125M removes may not be biodegradable

AIRCRAFT CLEANERS & DISINFECTANTS

ZIP-STRIP™ 125M



Page 3 of 4

Product description:

WATER RINSEABLE CIC REMOVER

PHYSICAL PROPERTIES:

► Appearance: Clear liquid

▶ Bulk Density: 7.0 lbs per gallon (839 grams per liter)

Composite Vapor Pressure: 0.5 mm of Hg @ 25°C (77°F)

► Flash Point: 127°F (53°C) PMCC

Odor: Solvent Odor

▶ Shelf Life: 3 Years From Date Of Shipment If Properly Stored

► Specific Gravity: 0.84

Viscosity: 200 cps.

▶ VOC Grams / Liter: 253 grams/liter (2.1 lbs/gallon)

► Volatiles: 87% by weight



ZIP-STRIP™ 125M



Page 4 of 4

Product description:

WATER RINSEABLE CIC REMOVER

AVAILABLE PACK SIZES:

Zip-Strip™ 125M

- Case of 12 of 16 fl oz (473 mL) Aerosols-102614
- Case of 4 each Gallon (4 each of 4.8 Liter) Cans-102608
- ► 5 Gallon (18.9 Liter) Pails-102609
- ▶ 55 Gallon (208 Liter) Drums-102610
- Special Packaging Upon Request

Formit®

- ► 12 Assemblies Per Package
- Formit® Sample Pack with 3 each of Formit®-18-F,

Formit®-18-180, Formit®-18-360,

and Formit®-18 STD-Fog-100107

