

### SUR-PREP® 5602



## Product description: ELECTRO-FREEZE

### FEATURES:

- ▶ Reduces surface temperatures to -50°F (-45°C )
- ▶ Portable

### KEY BENEFITS:

- ▶ An effective aid in locating defective electronic components
- ▶ Sur-Prep® 5602 lends itself to field service and manufacturing due to its portability
- ▶ Removes adhesives and sticky substances, such as gum from substrates



### SPECS:

• A-A-58060	• Boeing DPM 6372
• AHRI Standard 700-2019	• UAL GAS 3001-SC



Green  
Solution

### APPLICATIONS:

- ✓ Spray Sur-Prep® 5602 onto electronic component and observe for rapid evaporation and heating caused by an overheated part
- ✓ Sur-Prep® 5602 freezes substrates to remove adhesives and sticky substances, such as gum, so that the frozen material can be scraped from the substrate
- ✓ Use scraper to scrape off gum and sticky surfaces after spraying them with Sur-Prep® 5602
- ✓ Use in electronics, aerospace, power transmission, communications, and automotive industries
- ✓ Store Sur-Prep® 5602 at 40°F - 100°F (4.4°C- 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect Sur-Prep® 5602 from direct sunlight.

Rev: 20082I  
12-10-2025



For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)

### SUR-PREP® 5602



#### *Product description:* **ELECTRO-FREEZE**

#### **PHYSICAL PROPERTIES:**

- ▶ **Appearance and Odor:** Colorless w/slight ether odor
- ▶ **Boiling Point:** -25 °C (-13 °F) at 1,013 hPa.
- ▶ **Evaporation Rate:** Faster than ether
- ▶ **Flash Point:** < -50 °C (< -58 °F)
- ▶ **Material VOC:** None
- ▶ **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored
- ▶ **Specific Gravity:** 0.91
- ▶ **Vapor Density:** Heavier than air

#### **AVAILABLE PACK SIZES:**

- ▶ Case of 12 of 10 fl oz (296 mL) Aerosols-102533
- ▶ Special Packaging Upon Request



For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)