

Safety Steps and Procedures To Follow Prior To Applying D-5261NS/ZC-5261:

Always refer to the safety data sheet (SDS) prior to applying **D-5261NS/ZC-5261** if you have any questions regarding the following safety and regulatory information about this product.

Always wear gloves and protective eyewear to prevent **D-5261NS/ZC-5261** from making contact with the skin and eyes.

Always ensure that there is proper airflow in the area where **D-5261NS/ZC-5261** will be applied and always wear respiration equipment in areas with insufficient ventilation.

Make sure there are no sparks, open flames, hot surfaces, or other heat and fire ignition sources in the area where **D-5261NS/ZC-5261** will be applied.

D-5261NS/ZC-5261 Product Information and Benefits:

D-5261NS/ZC-5261 is a highly penetrating cleaning lubricant and solvent that deposits a rust preventive lubricating film, ensures that parts do not rust, prevents rusting and corroding on metals, and is a very effective cleaner and penetrating lubricant.

D-5261NS/ZC-5261 can be used in temperatures from -65°F (-54°C) to 250°F (121°C) and penetrates tight parts, such as heart strands of cables.

D-5261NS/ZC-5261 limits galvanic corrosion from occurring on dissimilar metal assemblies and provides superior resistance to oxidation.


Areas Where D-5261NS/ZC-5261 Can Be Applied:

D-5261NS/ZC-5261 can be used on metals including dissimilar metal assemblies, heart strands of cables, flight controls, pulleys, hinges, engine and landing gear cables, pressure seals, cargo hoist cables, cargo restraining system components, static joints, slide mechanisms, and door interlock actuating mechanisms.

Methods For Applying D-5261NS/ZC-5261:

D-5261NS is the aerosolized form of **ZC-5261** and can be spray applied or used in conjunction with the **Formit®** extension wands that are for use with all **Zip-Chem®** aerosols to reach difficult to access areas.

- * **Formit®** 360° Spray (White Tube) Wand
- * **Formit®** Fan Spray (Blue Tube) Wand
- * **Formit®** 180° Spray (Black Tube) Wands



Formit® 360° Spray
Demonstration Video



Formit® Fan Spray
Demonstration Video



Formit® 180° Spray
Demonstration Video



ZC-5261 is the bulk form of **D-5261NS** and can be applied via spray equipment and other bulk application equipment.

D-5261NS/ZC-5261 Instruction Manual

D-5261NS/ZC-5261 Product Pictures and Zip-Chem® Product Packaging Part Numbers:

D-5261NS

*Case of 12 of 16 fl oz (473 mL) Aerosols-**002056**

ZC-5261

*Case of 4 each Gallon (4 each of 3.8 Liter) Cans-**009425**

*5 Gallon (18.9 Liter) Pail-**002138**

*Special packaging upon request

Gloves | Protective Eyewear | Respirating Equipment

Ventilating Equipment | Spray and Bulk Application Equipment

Formit®

*Formit®-18-Fan-006224

*Formit®-18-180-006226

*Formit®-18-360-006227

*Formit®-18-STD-FOG-008352

*Formit®-18-90-FOG-008353

*Formit®-48-Fan-008460

*Formit®-29-360-101321

*Formit®-36-360-009131

*Formit®-48-360 with metal sleeve-**009132**

*Formit®-48-360 without metal sleeve-**100424**

*Formit® Sample Pack (3 each of Formit®-18-Fan, Formit®-18-180, Formit®-18-360, Formit®-18-STD-FOG-**100107**

Formit® NSN's: 4730-01-612-9914, 4730-01-661-8773 (Formit®-18-Fan)
6850-01-492-2942 (Formit®-18-360)
4730-01-632-0156 (Formit®-18-STD-FOG)
1560-01-658-8943 (with metal sleeve)

4730-01-659-5461 (without metal sleeve) (Formit®-48-360)
4730-01-632-0157 (Formit®-48-Fan)



D-5261NS 16 fl oz (473 mL) Aerosol

ZC-5261 1 Gallon (3.8 Liter) Can



For application questions regarding the D-5261NS/ZC-5261, contact Zip-Chem® Aviation Products at (1) 408 782 2335 or zipchem@addevmaterials.com