

## Safety Steps and Procedures To Follow Prior To Applying D-5263NS/ZC-5263:

Always refer to the safety data sheet (SDS) prior to applying **D-5263NS/ZC-5263** if you have any questions regarding the following safety and regulatory information about this product.

Always wear gloves and protective eyewear to prevent **D-5263NS/ZC-5263** from making contact with the skin and eyes.

Always ensure that there is proper airflow in the area where **D-5263NS/ZC-5263** will be applied and always wear respiration equipment in areas with insufficient ventilation.

Make sure there are no sparks, open flames, hot surfaces, or other heat and fire ignition sources in the area where **D-5263NS/ZC-5263** will be applied.

## D-5263NS/ZC-5263 Product Information and Benefits:

**D-5263NS/ZC-5263** is an aircraft cable lubricant and rust preventive that consists of a special formulation containing a blend of oils and is a general purpose, low temperature, and water displacing preservative oil.

**D-5263NS/ZC-5263** has a wide temperature range of -70°F to 300°F (-57°C to 149°C), protects internal applications up to 6 months, and maximizes life for all aircraft cables.

**D-5263NS/ZC-5263** can be used as a lubricant and rust preventive for general aircraft applications, such as cables.

## Areas Where D-5263NS/ZC-5263 Can Be Applied:

**D-5263NS/ZC-5263** can be used on cables, precision machine parts, cleaning pylon bearing prior to lubrication, cargo door hinges, door cable lubrication, lubricating safety blocker installation on tail cone work platform, small guns, machine guns, flap tracks, and jackscrews.


## Methods For Applying D-5263NS/ZC-5263:

**D-5263NS** is the aerosolized form of **ZC-5263** and can be spray applied or used in conjunction with the **Formit®** extension wands that are for use with all **Zip-Chem®** aerosols to reach difficult to access areas.

\* **Formit®** 360° Spray (White Tube) Wand

\* **Formit®** Fan Spray (Blue Tube) Wand

\* **Formit®** 180° Spray (Black Tube) Wands



**Formit® 360° Spray**  
Demonstration Video



**Formit® Fan Spray**  
Demonstration Video



**Formit® 180° Spray**  
Demonstration Video



**ZC-5263** is the bulk form of **D-5263NS** and can be applied via spray equipment and other bulk application equipment.

# D-5263NS/ZC-5263 Instruction Manual

## D-5263NS/ZC-5263 Product Pictures and Zip-Chem® Product Packaging Part Numbers:

### D-5263NS

\*Case of 12 of 16 fl oz (473 mL) Aerosols-**002057**

### ZC-5263

\*Case of 4 each Gallon (4 each of 3.8 Liter) Cans-**009426**

\*5 Gallon (18.9 Liter) Pail-**002141**

\*55 Gallon (208 Liter) Drum-**002142**

\*Special packaging upon request

Gloves | Protective Eyewear | Respirating Equipment

Ventilating Equipment | Spray and Bulk Application Equipment

### Formit®

\*Formit®-18-Fan-006224

\*Formit®-18-180-006226

\*Formit®-18-360-006227

\*Formit®-18-STD-FOG-008352

\*Formit®-18-90-FOG-008353

\*Formit®-48-Fan-008460

\*Formit®-29-360-101321

\*Formit®-36-360-009131

\*Formit®-48-360 with metal sleeve-**009132**

\*Formit®-48-360 without metal sleeve-**100424**

\*Formit® Sample Pack (3 each of Formit®-18-Fan, Formit®-18-180,

Formit®-18-360, Formit®-18-STD-FOG-100107

Formit® NSN's: 4730-01-612-9914, 4730-01-661-8773 (Formit®-18-Fan)

6850-01-492-2942 (Formit®-18-360)

4730-01-632-0156 (Formit®-18-STD-FOG)

1560-01-658-8943 (with metal sleeve)

4730-01-659-5461 (without metal sleeve) (Formit®-48-360)

4730-01-632-0157 (Formit®-48-Fan)



← D-5263NS 16 fl oz (473 mL) Aerosol

ZC-5263 1 Gallon (3.8 Liter) Can →



For application questions regarding the **D-5263NS/ZC-5263**, contact Zip-Chem® Aviation Products at (1) 408 782 2335 or [zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)



Part of



**ADDEV**  
MATERIALS