

## Safety Steps and Procedures To Follow Prior To Applying D-5633NS/ZC-633:

Always refer to the safety data sheet (SDS) prior to applying the **D-5633NS/ZC-633** if you have safety questions.

Always wear gloves and protective eyewear to prevent **D-5633NS/ZC-633** from contacting the skin and eyes.

## D-5633NS/ZC-633 Features and Benefits:

**D-5633NS/ZC-633** is an aviation grade aqueous based surface preparation cleaner that is formulated using Attar-C™ as the main ingredient, replaces chlorinated, petroleum distillate, terpene based, and hydrocarbon/surfactant blend solvents, and is designed for use at ambient temperatures.

**D-5633NS/ZC-633** is biodegradable non-flammable, non-toxic, has a mild odor, has no special storage or handling requirements, and contains no quantities of any reportable chemical under SARA Title III.

**D-5633NS/ZC-633** is safe on all metal and composite surfaces, contains a low VOC (<250 g/L) (2.0 lbs/gal), and is 100% water soluble.

## Procedures Areas Where D-5633NS/ZC-633 Can Be Applied:

**D-5633NS/ZC-633** should be applied in the following areas

- Metal
- Composite Surfaces
- General aircraft surfaces that are contaminated with very heavy deposits of oil, grease, hydraulic fluids, or baked-on carbon residues
- Wipe down applications for thrust reversers or body panels

## Procedures For Applying The D-5633NS/ZC-633:

A non-metallic brush or a cloth is recommended for applying **D-5633NS/ZC-633** because this method will agitate the material. For extremely soiled areas, a **5-10 minute dwell time** may be required.

If **D-5633NS/ZC-633** is used to prepare a surface, then a **water rinse** after applying **D-5633NS/ZC-633** is recommended.

Pre-test **D-5633NS/ZC-633** prior to applying the material on surfaces to ensure it is compatible with substrate it will be applied on.


## Methods For Applying D-5633NS/ZC-633:

**D-5633NS** comes in aerosol packaging and can be applied via the following methods:

\*Spraying

\***Formit®** extension wands that are for use with all **Zip-Chem®** aerosols to reach difficult to access areas.

- \* **Formit®** 360° Spray (White Tube) Wand
- \* **Formit®** Fan Spray (Blue Tube) Wand
- \* **Formit®** 180° Spray (Black Tube) Wands



**Formit® 360° Spray**  
Demonstration Video



**Formit® Fan Spray**  
Demonstration Video



**Formit® 180° Spray**  
Demonstration Video



**ZC-633** comes in bulk containers and can be applied using airless, air assist, HVLP, and any other spray or bulk application equipment used to apply paint and other coatings.

## D-5633NS/ZC-633 Packaging Pictures and Other Materials To Purchase:

### D-5633NS/ZC-633

- \*Case of 12 of 16 fl oz (473 mL) Aerosols-**002069 (D-5633NS)**
- \*Case of 4 each Gallon (4 each of 3.8 Liter) Cans-**007343 (ZC-633)**
- \*5 Gallon (18.9 Liter) Pails-**002152 (ZC-633)**
- \*Special packaging upon request (**ZC-633**)

Gloves | Protective Eyewear | Rag and Wiping Materials

Spray and Bulk Application Equipment | Rinsing Equipment

### Formit®

- \*Formit®-18-Fan-006224
- \*Formit®-18-180-006226
- \*Formit®-18-360-006227
- \*Formit®-18-STD-FOG-008352
- \*Formit®-18-90-FOG-008353
- \*Formit®-48-Fan-008460
- \*Formit®-36-360-009131
- \*Formit®-48-360 with metal sleeve-**009132**
- \*Formit®-48-360 without metal sleeve-**100424**
- \*Formit®-29-360-101321
- \*Formit® Sample Pack (3 each of Formit®-18-Fan, Formit®-18-180, Formit®-18-360, Formit®-18-STD-FOG-100107)

Formit® NSN's: 4730-01-612-9914, 4730-01-661-8773 (Formit®-18-Fan)  
 6850-01-492-2942 (Formit®-18-360)  
 4730-01-632-0156 (Formit®-18-STD-FOG)  
 1560-01-658-8943 (with metal sleeve)  
 4730-01-659-5461 (without metal sleeve) (Formit®-48-360)

4730-01-632-0157 (Formit®-48-Fan)

← D-5633NS 16 fl oz (473 mL) Aerosol

ZC-633 1 Gallon (3.8 Liter) Can →



For application questions regarding the D-5633NS/ZC-633, contact Zip-Chem® Aviation Products at (1) 408 782 2335 or zipchem@addevmaterials.com.