

D-5035NS



Page 1 of 3

Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

FEATURES:

- ▶ A heat resistant corrosion preventive
- ▶ Provides a firm and waxy coating

KEY BENEFITS:

- ▶ **D-5035NS** is formulated to provide long term protection against corrosion
- ▶ The **D-5035NS** coating can withstand continuous temperatures up to **350°F (177°C)**, with a short term exposure up to **430°F (221°C)**
- ▶ The **D-5035NS** coating contains excellent moisture displacing qualities and adhesion capabilities
- ▶ Free of chromates
- ▶ Free from heavy metals
- ▶ Low toxicity
- ▶ The **D-5035NS** coating provides over **1300 hours** of protection on steel in a salt fog environment
- ▶ The **D-5035NS** coating provides superior dampening to metal
- ▶ The **D-5035NS** coating contains acid neutralization properties



SPECS:

- Boeing QPL for DPM 5217
- NSN: 8030-01-686-7249 (16 fl oz (473 mL) Aerosol)

Rev: 20071K
06-17-2026

 For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS

D-5035NS



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

APPLICATIONS:

- ✓ A dry film thickness of **1.0 mil (25 microns)** provides a transparent coating
- ✓ The **D-5035NS** aerosol can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information. The **D-5035NS** aerosol can also be used with the **Zip-Chem® Aerosol Trigger Sprayer** which is designed for use with any **Zip-Chem®** aerosol can.
- ✓ Bulk application available as **ZC-035**
- ✓ Firm and waxy coating of **D-5035NS** can be easily removed with petroleum solvents
- ✓ Refer to the **D-5035NS** application manual for detailed application instructions. This manual can be obtained by asking your **Zip-Chem®** sales rep for a copy of this document.
- ✓ Store **D-5035NS** at **40°F-100°F (4.4°C-37.8°C)** in the original unopened containers. Keep containers closed when not in use and protect **D-5035NS** from direct sunlight.

PHYSICAL PROPERTIES:

- ▶ **Evaporation Rate:** Faster Than Ether
- ▶ **Fungal Growth per Fed-STD-810 Method 508.7:** 0 (No Microbial Growth)
- ▶ **Material V.O.C.:** 583 grams / Liter (4.8 lbs/gal)
- ▶ **Melt Point:** 550°F (28°C)
- ▶ **Specific Gravity:** 0.8
- ▶ **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored
- ▶ **Vapor Density:** Heavier Than Air

D-5035NS



Product description:
HIGH TEMPERATURE CORROSION PREVENTIVE

AVAILABLE PACK SIZES:

D-5035NS

- ▶ Case of 12 of 16 fl oz (473 mL) Aerosols-002052




ZC-035

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Cans-002115
- ▶ 5 Gallon (18.9 Liter) Pail-002116
- ▶ 55 Gallon (208 Liter) Drum-002117
- ▶ Special Packaging Upon Request

Formit®

- ▶ 12 Assemblies Per Package
- ▶ **Formit® Sample Pack** with 3 each of **Formit®-18-F**, **Formit®-18-180**, **Formit®-18-360**, and **Formit®-18 STD-Fog-100107**



Zip-Chem® Aerosol Trigger Sprayer

- ▶ 010040