



AIRCRAFT CLEANERS & DISINFECTANTS

CALLA® 602LF



Page 1 of 3

Product description:

HEAVY DUTY CLEANING AND DEGREASING COMPOUND FOR AQUEOUS PARTS CABINETS

FEATURES:

- ▶ A concentrated cleaner for use in aqueous parts washing cabinets

KEY BENEFITS:

- ▶ Safe to use to clean various aircraft substrates including magnesium, IVD aluminum coated steel, cadmium plated steel, aluminum, titanium, and other high strength materials
- ▶ **Calla® 602LF's** low VOC formulation allows it to be used in the strictest air quality control regulations
- ▶ Low foaming at temperatures as low as **140°F (60°C)**
- ▶ Removes dirt and grease from parts with cycle times as low as **3 minutes**
- ▶ A short term emulsifier that allows for easier separation of the greases and oils from the waste stream



SPECS:

- NSN: 6850-01-513-5230 (1 Gallon (3.8 Liter) Bottle)
- NSN: 6850-01-513-5237 (5 Gallon (18.9 Liter) Pail)
- NSN: 6850-01-513-5233 (55 Gallon (208 Liter) Drum)
- Meets Mil-C-29602 except section 3.7 (pH)
- Source Control Drawing 9825019-17, -19 & -21 Rev. C (Meets all requirements)
- T.O. 4W-1-161 (Meets all requirements)
- T.O. 4B-1-32 (Meets all requirements)
- T.O. 4S-1-182 (Meets all requirements)

Rev: 20076H
09-16-2026



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



AIRCRAFT CLEANERS & DISINFECTANTS

CALLA® 602LF



Page 2 of 3

Product description:

HEAVY DUTY CLEANING AND DEGREASING COMPOUND FOR AQUEOUS PARTS CABINETS

APPLICATIONS:

- ✓ The operating temperature of **Calla® 602LF** is **140°F - 160°F (60°C-71°C)**.
- ✓ Use at **5%** dilution (Especially for optimum cleaning efficiency)
- ✓ Apply **Calla® 602LF Defoamer (010021)** to solution if it generates too much foam. That way, the foam can be reduced.
- ✓ Usual cycle time for cleaning is **3-15 minutes**.
- ✓ **100 Gallon (378.5 Liter) Tank Parts Washer: 5 gallons (18.9 Liters)** of **Calla® 602LF** should be added, and then top off by adding the balance in water.
- ✓ Please refer to the **Calla® 602LF** application manual for detailed application instructions. This manual can be obtained by reaching out to your **Zip-Chem®** rep for a copy of this document.
- ✓ Store **Calla® 602LF** at **40°F - 120°F (4.4°C – 49.0°C)** in the original containers. Keep containers closed when not in use and protect **Calla® 602LF** from direct sunlight.

PHYSICAL PROPERTIES:

- ▶ **Density:** 8.5 lbs/gal (1018 grams / Liter)
- ▶ **Flash Point:** No Flash Point
- ▶ **Non-Volatiles:** 20%
- ▶ **Operating Temperature:** 140°F - 160°F (60°C-71°C)



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS



AIRCRAFT CLEANERS & DISINFECTANTS

CALLA® 602LF



Page 3 of 3

Product description:

HEAVY DUTY CLEANING AND DEGREASING COMPOUND FOR AQUEOUS PARTS CABINETS

PHYSICAL PROPERTIES (CONTINUED FROM PAGE 2):

- ▶ **pH:** 6.5 - 8.0
 - ▶ **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored
 - ▶ **Surface Tension (dynes/cm):** 20 (For 5% Solution)
-

AVAILABLE PACK SIZES:

Calla® 602LF

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Bottles-009437
- ▶ 5 Gallon (18.9 Liter) Pail-008935
- ▶ 55 Gallon (208 Liter) Drum-008936
- ▶ 330 Gallon (1249 Liter) Tote-008937
- ▶ Special Packaging Upon Request

Calla® 602LF Defoamer

- ▶ Case of 4 each Gallon (4 each of 3.8 Liter) Bottles-010021



For more information contact us :
zipchem@addevmaterials.com



Part of



ADDEV
MATERIALS