

LUBRICANTS & LUBRICATING COMPOUNDS

ZC-460



Product description:

MOLY DRI-LUBE

FEATURES:

- A resin-bonded system of molybdenum disulfide powder that is dispersed in a thermoplastic resin which air dries in 5-10 minutes
- Contains a dry film
- An extreme pressure lube

KEY BENEFITS:

- Excellent high temperature stability
- Good surface adhesion
- Excellent for use as a break-in lube, rubber anti-seize, and gasket coating
- Contains a fast drying formula
- Yields a thin but durable abrasion resistant coating that is effective up to 660°F (350°C)

SPECS:

- GE Aviation GE/DFO: A50 TF192 Class C-6, 192-58
- UAL#: LUB-4500-12SC

APPLICATIONS:

- ✓ Aerosol application available as **D-5460NS**
- ✓ Originally formulated for DC-8 flap track fairings

Rev: 20069L
12-16-2025

For more information contact us :
zipchem@addevmaterials.com

ZIP CHEM Part of & ADDEV MATERIALS



ZC-460

Product description:

MOLY DRI-LUBE

APPLICATIONS (CONTINUED FROM PAGE 1):

- ✓ Used in aircraft applications, which includes DC-10 elevator bus support system parts (springs and quick tubes) and engine applications, such as fan rotor assembly and fan reverser pre-cooler duct seal lubrication
- ✓ Store **ZC-460** at 40°F - 100°F (4.4°C - 37.8°C) in the original unopened containers. Keep containers closed when not in use and protect **ZC-460** from direct sunlight.

PHYSICAL PROPERTIES:

- **Average Particle Size:** MoS_2 (0.4 Microns (0.01 Mils))
- **Coefficient of Friction:** .23 (Static)
- **Color:** Gray
- **Service Temp:** 390°F (200°C)
- **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored

AVAILABLE PACK SIZES:

D-5460NS

- Case of 12 of 16 fl oz (473 mL) Aerosols-002061

ZC-460

- Case of 4 each Gallon (4 each of 3.8 Liter) Cans-002318
- Special Packaging Upon Request

For more information contact us :
zipchem@addevmaterials.com

ZIP CHEM Part of & ADDEV MATERIALS