

Cor-Ban®

CORROSION INHIBITING COMPOUNDS

D-5029NS



Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

FEATURES:

- A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- Non-tacky with a light, amber tint

KEY BENEFITS:

- Fast drying and non-tacky
- Non-cracking and flaking up to **-40°F (-40°C)**
- Free of chromates
- Free from heavy metals
- Low toxicity
- Contains a detectable film
- Solvent removable
- **> 1500 hours** of salt spray
- High Solids **> 51%**

Rev: 29094H
11-04-2026

For more information contact us :
zipchem@addevmaterials.com

ZIP CHEM Part of ADDEV MATERIALS



D-5029NS

Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

SPECS:

- Boeing BMS 3-29
- Boeing DMS 2150 Type 1 & Type 2
- NSN: 8030-01-501-6622

APPLICATIONS:

- ✓ Use **D-5029NS** on high profile aircraft substrates
- ✓ Easily apply corrosion inhibiting compound via aerosol
- ✓ **D-5029NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information. **D-5029NS** can also be used in conjunction with the **Zip-Chem® Aerosol Trigger Sprayer** that is designed for use with any **Zip-Chem®** aerosol can.
- ✓ Apply at **2-3 mils (51-76 microns)** of wet thickness. This wet thickness can be measured with **Zip-Chem®** 's **Wet Film Thickness Gauge**.
- ✓ **One aerosol can** coats **approximately 50 ft² (4.7m²)**
- ✓ Bulk application available as **ZC-029**
- ✓ Please refer to the **D-5029NS** application manual for detailed application instructions. This manual can be obtained by reaching out to your **Zip-Chem®** for a copy of this document.
- ✓ Store **D-5029NS** at **40°F to 100°F (4.4°C - 37.8°C)** in the original unopened containers. Keep containers closed when not in use and protect **D-5029NS** from direct sunlight.

For more information contact us :
zipchem@addevmaterials.com

ZIP CHEM Part of & ADDEV MATERIALS



D-5029NS

Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

PHYSICAL PROPERTIES:

- **Color:** Transparent Amber
- **Drying Time:** <12 hours
- **Flash Point:** 122°F (50°C)
- **Non-Volatiles:** 51% min.
- **Shelf Life:** 3 Years From Date Of Shipment If Properly Stored
- **Specific Gravity:** 0.89
- **Viscosity:** 140 cps.
- **Water Displacement:** 0% Rust

AVAILABLE PACK SIZES:

D-5029NS

- Case of 12 of 16 fl oz (473 mL) Aerosols-002050

For more information contact us :
zipchem@addevmaterials.com

ZIP CHEM Part of ADDEV MATERIALS

D-5029NS

Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

AVAILABLE PACK SIZES (CONTINUED FROM PAGE 3):

ZC-029

- Case of 4 each Gallon (4 each of 3.8 Liter) Cans-009422
- 5 Gallon (18.9 Liter) Pail-002109
- 55 Gallon (208 Liter) Drum-002110
- Special Packaging Upon Request

Zip-Chem® Aerosol Trigger Sprayer

- 010040

Wet Film Thickness Gauge

- 100266

Formit®

- 12 Assemblies Per Package



- **Formit® Sample Pack** with 3 each of **Formit®-18-F**, **Formit®-18-180**, **Formit®-18-360**, and **Formit®-18 STD-Fog**-100107





